ThinkCentre M700 Tiny Platform Specifications

Processor	Intel® Celeron®, In	tel Pentiu	m [®] , or 6th Gener	ation Intel	Core™ i3 / i5 / i	7 Processor	Keyboard	Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo	
	Processor Cores / Frequence Threads Base/Max(C			Casha	Memory Types	Integrated Graphics		Some: Lenovo Slim USB Keyboard (ÙSB connector), black, Lenovo logo Some: Lenovo USB Fingerprint Keyboard (USB connector)	
	Pentium G4400T	2/2	2.9 G	3 MB	DDR4-2133	HD 510	Mouse	Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black Some: Enhanced Optical USB Mouse, black, Lenovo logo	
	Pentium G4500T	2/2	3.0 G	3 MB	DDR4-2133	HD 530		<i>Some:</i> Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	
	Core i3-6100T	2/4	3.2 G	3 MB	DDR4-2133	HD 530	Mechanical	Tiny (1L), black color; metal case	
	Core i3-6300T	2/4	3.3 G	4 MB	DDR4-2133	HD 530	moonanioar	M700 Tiny only:	
	Core i5-6400T	4/4	2.2 G / 2.8 G	6 MB	DDR4-2133	HD 530		7.05" W X 7.20" D X 1.36" H	
	Core i5-6500T	4/4	2.5 G / 3.1 G	6 MB	DDR4-2133	HD 530		179mm W X 182.9mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration	
	Core i5-6600T	4/4	2.7 G / 3.5 G	6 MB	DDR4-2133	HD 530		With VESA mount & ODD box:	
	Core i7-6700T	4/8	2.8 G / 3.6 G	8 MB	DDR4-2133	HD 530		7.42" W X 7.30" D X 2.48" H	
Memory	32GB max, DDR4 2133, two 260-pin SO-DIMM sockets, dual-channel capable					capable	VESA mount Floor Stand Optional system floor stand for vertical orientation		
Disk Optical	 Some: SATA 6.0Gb/s, 2.5" Wide, 5400 rpm or 7200 rpm Some: 500GB (5400 rpm) Solid State Hybrid Drive (SSHD) / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: M.2 Solid State Drive (SSD) / SATA interface Some: external ODD box with DVD-ROM, 9.5mm high, via USB Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB 								
optiour						SB	Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models) 90 watts AC/DC adapter, autosensing, 88% PSU (only for models with I/O box)	
Onboard SATA						B			
Media reader	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar None					anar	Linned warranty	Some: 1-year or 3-year, limited onsite service / service upgrades available Some: 3-year, limited onsite service, OID (Onsite International Delivery) / service upgrades available For Lenovo service upgrade options, please go to S-TC sheet	
Graphics	Intel HD Graphics 510/530 in processor, uses main memory, DirectX [®] 12, two DisplayPort™, one optional HDMI, VGA, or 3rd DP, up to 3 independent displays; <i>Max resolution:</i> 4096x2304 (DP)@60Hz; 4096x2160 (HDMI)@24Hz;								
DP cable	1920x1200 (VGA)@60Hz Optional DP to VGA, DP to DVI-D (single link), or DP to HDMI 1.4 dongle					gle	Preload	Some: Windows [®] 7 Professional 32/64 Some: Windows [®] Embedded preinstalled through downgrade Standard 7 (WES 7)	
Chipset	Intel B150 Chipset							rights in Windows 10 Pro 64-bit Some: LeTOS (Lenovo Terminal Some: Windows 7 Professional 32/64 Operating System, Linux-based)	
Front ports	Two USB 3.0 (one is Always On and fast charge), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)					ereo, 3.5mm),		Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Iisted)	
Rear ports	Four USB 3.0 (optional external optical box or external I/O box occupies one or two specific USB 3.0 on some models), ethernet (RJ-45), two DisplayPort,							Preloaded applications (only some listed) - WES 7 only: • RDP Client (RDP 8.1 support)	
I/O box	one optional port (VGA, 3rd DP, HDMI, or serial on some models), one headphone Optional external I/O box, extends two USB 2.0, two USB 3.0, and one serial on rear, two USB 2.0 on front, via USB (occupy two specific USB 3.0 of M700 Tiny)							 Desktop Power Manager Lenovo Solution Center Lenovo REACHit Citrix Client VMware Client Internet Explorer 11 	
Audio support	High Definition (HD) Audio, Realtek ALC223 / optional internal speaker (1 watt)							Lenovo SHAREit Java	
WLAN ¹³	 Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, 					,.		 Lenovo Bluetooth Lock (for models with Wi-Fi/BT card) McAfee[®] LiveSafe[™] (30-day trial) Microsoft Office preloaded; purchase a product key to activate PowerDVD Create (DVD±RW) Lenovo ThinkVantage Tools Intel Unite (vPro models only) Flash Net Framework Microsoft[®] Silverlight Echo Agent (client for LTM, Lenovo Thin Client Manager) Adobe Reader UltraVNC LeTOS only: 	
	Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8260, Wi-Fi + Bluetooth 4.1 combo adapter, 2x2							 Only for Window 10 Lenovo Companion Cyberlink PowerDVD (DVD, DVD±RW) VMware View Client 	
Bluetooth™ Ethernet Modem	Some: Bluetooth 4.0 or 4.1 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-LV (Jacksonville), Wake on LAN® None							 Lenovo QuickOptimizer Only for Window 7 Rescue and Recovery Java Mozilla Firefox 	
Manageability	None							 Password Manager ThinkVantage System Update 	
Security chip Security features	 Trusted Platform Module, TCG 1.2-compliant Security slot (in rear for optional Kensington® MicroSaver® cable) Padlock loop Smart USB protection, allows keyboard/mouse only, blocks all storage devices 							 Lenovo Message Center Plus Adobe® Reader® 	
							Environment	ENERGY STAR [®] 6.0*, EPEAT [™] Gold rating* (*for Windows models only); ErP Lot 3; GREENGUARD [®] ; RoHS-compliant	
	 Power-on passw 				intrusion switch		Accessories	For compatible accessories, please go to TC-AQP sheet	

See footnotes for more detailed information